

HERON™ HD3430

DATALOGIC
EMPOWER YOUR VISION



PERFORMANCE WITHOUT COMPROMISE

The Heron HD3430 2D area imager brings unmatched elegance along with the latest advanced 2D reading technology to the modern point-of-sale. The stylish silhouette of the new 2D area imager enriched with multiple color changing lights, innovative and modern design material, together with the audio speaker, amplifies the customer's brand experience at the point-of-sale.

NOW WITH 2D AND IMAGE CAPTURE

The Heron HD3430 2D area imager provides outstanding reading performance on 1D and 2D codes as well as image capture capabilities. Featuring the market's most efficient aiming and illumination systems, the Heron HD3430 2D area imager guarantees the operator's best suitability combined with an outstanding all-codes reading capability.

BEAUTY AND BRAND IDENTITY

The Heron HD3430 2D area imager differs from the usual color scheme of handheld devices by providing a stunning 'black' or 'white' color option, emphasizing the curving lines of the new enclosure. Additionally, the Heron imager features in-mold decorated top covers with a choice of 'Carbon Fiber' or 'Silver' design. This imager also offers opportunities to incorporate a company brand identity by allowing customers to compose the perfect blend: combining a company logo with the top cover color with customized visual and audio feedback in order to reinforce the value of the customer's brand.

The HD3430 2D area imager is a fusion of the features your business needs, the fashionable style customers will love, the enticing allure of light and sound now with a full 2D reading capability.

FEATURES

- Outstanding reading performance on 1D, 2D, postal codes, stacked and composite codes
- Innovative and unique design raises the bar for a cutting-edge POS checkout experience
- In-mold decorated top cover with 'carbon-fiber' or 'silver' look
- Multiple changing color LEDs on sides and top
- Polyphonic speaker for a wide variety of choices regarding audio feedback
- Easily customized with logo, top cover, visual and audio feedback
- Datalogic's patented 'Green Spot' technology for good-read feedback
- Automatic switching between handheld and hands-free operations
- Efficient illumination and aiming system
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY - APPLICATION

- Retail: Point of Sale for Fashion and Specialty Stores



HERON™ HD3430

TECHNICAL SPECIFICATIONS

| DECODING CAPABILITY | |
|--------------------------|---|
| 1D / Linear Codes | Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| 2D Codes | Aztec Code, Aztec Mesas, Data Matrix, MaxiCode, QR Code, Micro QR Code, China Han Xin Code |
| Postal Codes | Australian Post, British Post, Canadian Post, China Post, Japanese Post, KIX Post, Korea Post, Planet Code, Postnet, Royal Mail Code (RM4SCC) |
| Stacked Codes | EAN/JAN Composites, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, MacroPDF, MicroPDF417, PDF417, UPC A/E Composites |

| ELECTRICAL | |
|------------------------------|--|
| AC Power Requirements | Power Consumption: Operating (Maximum): <500 mA @ 5 V Operating (Typical): <300 mA @ 5 V Sleep Mode: < 2.5 mA |
| Input Voltage | 5 VDC +/- 5% |

| ENVIRONMENTAL | |
|---------------------------------------|--|
| Ambient Light | 0 - 100,000 lux |
| Drop Resistance | Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface. |
| ESD Protection (Air Discharge) | 16 kV |
| Humidity (Non-Condensing) | 5 - 90% |
| Particulate and Water Sealing | IP40 |
| Temperature | Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -20 to 70 °C / -4 to 158 °F |

| INTERFACES | |
|-------------------|---|
| Interfaces | Keyboard Wedge / OEM (IBM) USB / RS-232 / USB |

| PHYSICAL CHARACTERISTICS | |
|--------------------------|---|
| Colors Available | Black; White Other colors and custom logo options are available for minimum quantity purchase. |
| Dimensions | 15.2 x 15.3 x 6.8 cm / 6.0 x 6.0 x 2.7 in |
| Top Cap Design | Carbon-Fiber; Silver |
| Weight | 150.0 g / 5.3 oz |

| READING PERFORMANCE | |
|---------------------------------------|--|
| Image Capture | Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2 |
| Imager Sensor | Wide VGA: 752 x 480 pixels |
| Light Source | Aiming: 650 nm VLD; Illumination: White |
| Motion Tolerance | 25 IPS |
| Print Contrast Ratio (Minimum) | 15% |
| Reading Angle | Pitch: +/- 65°; Roll (Tilt): Up to +/- 360°; Skew (Yaw): +/- 60° |
| Reading Indicators | Beeppers, Polyphonic; Datalogic 'Green Spot' Good Read Feedback; Product side and upper illumination; Good Read LED |
| Resolution (Maximum) | 4 mils |

| READING RANGES | |
|-------------------------------|---|
| Typical Depth of Field | Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. Code 39: 5 mils: 3.5 to 20.0 cm / 1.3 to 7.8 in EAN-13: 13 mils: 3.0 to 40.0 cm / 1.2 to 15.7 in Data Matrix: 15 mils: 2.0 to 25.0 cm / 0.8 to 9.8 in |

| SAFETY & REGULATORY | |
|---------------------------------|---|
| Agency Approvals | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| Environmental Compliance | Complies to China RoHS; Complies to EU RoHS |
| Laser Classification | Class 2 according to IEC 60825-1 |
| LED Classification | Exempt group according to IEC 62471 |

| UTILITIES | |
|-----------------------------|---|
| Datalogic Aladdin™ | Datalogic Aladdin configuration program is available for download at no charge. |
| OPOS / JavaPOS | OPOS and JavaPOS utilities are available for download at no charge. |
| Remote Host Download | Lowers service costs and improves operations |

| WARRANTY | |
|-----------------|-------------------------|
| Warranty | 5-Year Factory Warranty |

ACCESSORIES

Mounts/Stands



STD-AUTO-H030-BK
AutoSense Stand Only, Black



STD-AUTO-H030-WH
AutoSense Stand Only, White



STD-AUTFLX-H030-BK
AutoFlex Stand, Black



STD-AUTFLX-H030-WH
AutoFlex Stand, White